



# Recommended Tapes and Substrates Compatibility

↓ Type of Fastener	Pressure Sensitive Adhesives																	Precoated Adhesives		
	Rubber-based Hotmelt							FR Rubber-based Hotmelt		Acrylic Water-based		Acrylic Solvent-based						Nitrile & PUR-based		
	PS-30	SA	PS-19	PS-10	PS-14	A	PS-51	PS-15	FRA	PS-18	ATA	PS-B8	PS-B4	AT	PS-5310	PS-5345	PS-6411	PC-20	PC-28	HF
Hook and Loop Fasteners (Polyamide yarns)	✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✓	✓	✗	✓	✗	✗	✗	✓	✓	✓
Hook FR and Loop FR Fasteners (Polyamide yarns)	✗	✗	✗	✓	✗	✗	✗	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Hook and Loop Fasteners (Polyester yarns)	✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✓	✗	✗	✓	✗	✗	✗	✓	✓	✓
Mushroom Hooks* (Polyester / Polypropylene yarns)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✗	✗	✗	✓	✓	✗
ALFA-LOK® Fastener	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓	✗	✗	✗
HTH Fasteners (Polypropylene or Polyethylene)	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✓	✓	✗	✗	✗	✗	✗	✓
HTH Fasteners (Polyamide)	✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✓	✗	✗	✓	✗	✗	✗	✗	✗	✓
Velours Heavy (440-285 g/m²)	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✗	✓	✗	✗	✗	✗	✗	✗
Velours Standards (250-230 g/m²)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✗	✗	✓	✗	✗	✗	✗	✗	✗
Velours Medium (210-190 g/m²)	✓	✗	✓	✓	✓	✗	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Velours Light (165-115 g/m²)	✓	✗	✓	✓	✓	✗	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Velours Extra Light (100-50 g/m²)	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗

↓ Type of Substrate	Pressure Sensitive Adhesives																	Precoated Adhesives		
	PS-30	SA	PS-19	PS-10	PS-14	A	PS-51	PS-15	FRA	PS-18	ATA	PS-B8	PS-B4	AT	PS-5310	PS-5345	PS-6411	PC-20	PC-28	HF
Aluminum Anodised	✓	✗	✓	✓	✓	✗	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗
Glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
Painted Wallboard	✓	✓	✓	✓	✓	✗	✓	✓	✗	✓	✗	✓	✓	✗	✓	✓	✓	✓	✓	✗
Plywood	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗
Polyester	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✗	✓	✓	✓	✓	✓	✗
Polyethylene	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✗	✗	✓	✓	✓	✓	✓	✗
Polypropylene	✓	✓	✓	✓	✓	✗	✓	✓	✓	✗	✗	✓	✗	✗	✓	✓	✓	✓	✓	✗
Stainless Steel	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✗	✓	✓	✓	✓	✓	✗
Vinyl	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Formica (Polished Side)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✗	✗	✓	✓	✗	✗	✗
Cardboard	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✗	✗	✓	✓	✓	✓	✗
Polyacrylic	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✗	✓	✓	✓	✓	✓	✗
Fabrics	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✓

\*For VELCRO® Brand VEL-LOC® mushroom hooks, only activate with solvent or weldable under 80 °C

✓ Recommended    ✓ Good    ✗ Not available